# **DSL**

## In-line Double Suction Centrifugal Pump DSL Vertically & Horizontally installed

The DSL pumps are singe-stage, double-suction, vertical, centrifugal pumps. The design of the suction side provides for a perfect flow, and the inlet is placed in line with the outlet. Add to this the advanced double-suction impeller and the result is high efficiency and low NPSH-values

#### Pump concept:

- Single-stage, double-suction, centrifugal pumps
- The design of the suction side provides for a perfect flow
- The inlet is placed in line with the outlet
- · Advanced double-suction impeller
- · High efficiency
- Low NPSH-values





DSL - Inline double suction centrifugal pump		
Nominal diameter (DN)	300 to 500	
Flow rate	Up to 5400 m³/h (23800 US gpm)	
Head	Up to 90 m (295 ft.)	
Pressure	Up to 25 bar (363 psi)	
Temperature	Up to 150°C (302°F)	
Applications: District heating/cooling, seawater, water circula-		

Applications: District heating/cooling, seawater, water circula-
tion, cooling towers distribution, chiller distribution, scrubber
(flue gas cleaning).

Standard Material Specifications		
Pump casing	Cast Iron	
Impeller	NiAl-Bronze	
Sealing ring	NiAl-Bronze	
Rear cover	Cast Iron	
Shaft	Stainless Steel	
Shaft seal	Mechanical	

Alternative material combinations are available

### Alternative materials include:

Cast Iron, Ductile Iron, Bronze, NiAl-Bronze, Stainless Steel, Super Duplex Stainless Steel

**DESMI** 

For more information on Utility/District Energy solutions, please visit www.desmi.com

MARINE & OFFSHORE INDUSTRY OIL SPILL RESPONSE DEFENCE & FUEL UTILITY

## **Production Technology**

The pumps are fitted with bearings and mechanical shaft seal at both top and bottom. This gives a robust construction, designed for trouble-free continuous duty. The pumps are radially split. In spacer design, service

The pumps are radially split. In spacer design, service including replacement of bearings and mechanical shaft seal, can be carried out without removing motor and piping.

Significant advantages to the benefit of the service personnel.

The DSL inline pumps can be mounted horizontally on request.









